

## ADHESION PROMOTING PRIMER

*This product has been designed to prime dry plaster, cement, brickwork and natural stone prior to the application of gypsum render. It consolidates the substrate and delivers excellent adhesion.*

### AVAILABILITY

<i>Appearance</i>	Clear.
<i>Packing</i>	5, 18litres.
<i>Pot Life</i>	Once opened the shelf life of this product is unpredictable.

### PROPERTIES

<i>Description</i>	A water-based, styrene acrylic copolymer concentrate to be diluted with clean water prior to application.
<i>Uses</i>	For interior, natural surfaces to be rendered in gypsum: <ul style="list-style-type: none"><li>○ Natural Stone</li><li>○ Concrete</li><li>○ Dry Plaster</li><li>○ Bricks</li></ul>
<i>Drying Time conditions.</i>	Touch dry in 2hrs. Gypsum render can be applied after 4hrs under normal
<i>Spread Rate</i>	When diluted as recommended, coverage is up to 10 sq. meters per litre depending on surface profile and porosity.
<i>Preparation</i>	Surface contaminants such as oil, grease, dirt etc. are to be removed using a degreasing agent. It is vital that the surface to be coated is clean and dry before coating. Dust from dry render or sanding must be removed prior to application. Previous renders must be fully cured before application of the primer.
<i>Application</i>	The product is supplied as a concentrate. Mix 1 part product with 4 parts clean water. Stir well. Apply by brush, roller or spray. Do not apply the product too thickly.

*Cleaning*

Clean all equipment with water immediately after use.

*Precautions*

This product is not intended as a primer for emulsion paints. Painting in damp or humid conditions may extend drying and overcoating times.

**No Lead Added. Does not contain sulphur hexafluoride (SF6).**