

AQUACRYL CEILING PAINT

A quick drying water paint for interior use, based on a new-generation styrene acrylic resin. Aquacryl offers superior brightness and opacity. Recommended for use over new rendering. Specially formulated to allow surface to 'breathe' and dry naturally.

AVAILABILITY

<i>Colour Range</i>	Brilliant white.
<i>Packing</i>	2.5Lt, 5 Lt and 15 Lts.

PROPERTIES

<i>Drying Time</i>	Touch dry in 2hrs and re-coatable after 4hrs under normal conditions.
<i>Spread Rate</i>	Up to 12 sq. metres per litre per coat depending on surface porosity and texture.
<i>Uses</i>	Suitable for the decoration and preservation of interior walls & ceilings.
<i>Application</i>	Supplied ready for use by brush, roller or conventional spray. For airless spray application, thin with up to 10% water. For brush or roller application where required by the type of surface, thin with up to 10% water. On very absorbent surfaces, the first coat may be thinned with up to 20% water.
<i>Cleaning</i>	Clean all equipment with water.

SPECIFICATIONS

<i>New Plaster, Plasterboard, Brickboard and Cement</i>	To the clean, dry, efflorescent-free surface, apply a mist coat (watered-down) coat of paint. Apply a further one to two coats of paint. Thin as recommended.
<i>Previously-Painted Surfaces</i>	Thoroughly wash off dirt, grease etc. and remove all loose and flaking paint. Apply 2 to 3 coats of paint. Cannot be applied on previous coats of washable emulsion paint.
<i>Distempered Surfaces</i>	Remove all loose and flaking paint. Carry out necessary repairs. Apply a mist coat to consolidate the surface. Apply two to three coats of water paint. Thin as recommended.

Precautions

Store away from temperature extremes.

Use only in well ventilated areas during spraying. In case of insufficient ventilation during spraying wear suitable respiratory equipment.
Do not breath vapour / spray.
In case of contact with eyes, rinse immediately with plenty of water, seek medical advice.
Keep out of reach of children.

No Lead Added