

## Concrete Dust Proofer

*A clear, modified acrylic dust proofer that seals and stabilises most concrete and stone surfaces. It also provides good resistance to light vehicular traffic when applied in multiple thin coats.*

### AVAILABILITY

<i>Colour Collections</i>	Clear only.
<i>Packing</i>	18 Litres.
<i>Pot Life</i>	Once opened the shelf life of this product is unpredictable.

### PROPERTIES

<i>Drying Time</i>	Touch dry in up to 2hrs and re-coatable after 4hrs under normal conditions. <i>Spread</i>
<i>Rate</i>	Up to 10 sq. meters per litre per coat depending on surface profile and porosity.
<i>Preparation</i>	Surface contaminants such as oil, grease, dirt etc. are to be removed using a degreasing agent. It is vital that the surface to be coated is clean and dry before coating. It is also recommended that the first coat is thinned with up to 15% clean water.
<i>Application</i>	Stir very well before use. Apply by brush or roller. May be thinned with up to 15% clean water for conventional or airless spray application.
<i>Cleaning</i>	Clean all equipment with water immediately after use.
<i>Precautions</i>	Painting in damp or humid conditions may extend drying and overcoating times. Rising damp will cause paint to lift.

Use only in well ventilated areas during spraying. In case of insufficient ventilation during spraying wear suitable respiratory equipment.  
Do not breath vapour / spray.  
In case of contact with eyes, rinse immediately with plenty of water, seek medical advice.  
Keep out of reach of children.

**No Lead Added**