

DOMAC FLEXIBLE ROOF COMPOUND

A highly elastic membrane providing a seamless waterproof finish. Domac is intended for the waterproofing of flat roofs.

AVAILABLILITY

Colour Range Green, Grey, Magnolia and White.

Packing 2.5 Litre, 5 Litre, 10 Litre and 20 Litre.

PROPERTIES

Drying Time Surface dry in 2-3 hours, re-coatable after 12 hours under normal conditions.

Spread Rate 5-8 sq. metres per litre per coat dependent on surface porosity and texture when

applied by brush.

Uses Intended for concrete flat roofs, terraces with adequate water run off. It is not

intended for tiled areas. Very smooth, power-floated roofs might require the application of a primer for improved adhesion. Domac is not intended to be used in ponds, reservoirs, swimming pools or other applications where water-ponding is

present. Not intended for contact with potable water.

Preparation Repair all cracks and structural defects. Surface must be dry and free from dust,

loose and flaking material, dirt, grease and organic growth. Washing and

adequate drying of the substrate is highly recommended.

Application Stir contents thoroughly and apply by brush or roller. Two coats are normally

recommended for best results. Do not apply below 10°c and where the relative humidity may cause surface condensation, or where there is a threat of heavy rain.

The first coat may be diluted with up to 20% of fresh clean water and the second

coat with up to 10%.

Do not apply any "Sealer" before the application of Domac.

Do not add / mix any "Sealer" with Macpherson Domac.

Clean all equipment with soap and water immediately after use.

Precautions

Store away from temperature extremes.

Use only in well ventilated areas during spraying. In case of insufficient ventilation during spraying wear suitable respiratory equipment.

Do not breath vapour / spray.

In case of contact with eyes, rinse immediately with plenty of water, seek medical advice. Keep out of reach of children.

No Lead Added

