

DURAKOTE SMOOTH

A durable, water-borne exterior wall paint containing a styrene acrylic resin and quality extenders and pigments providing a weather resistant ultra smooth coating that minimises dirt pick up. It has excellent whiteness and hiding power. Durakote contains dry film biocides to combat algae and fungal growth.

AVAILABILITY

Colour Range Brilliant White and Magnolia

Packing 2.5, 5, 10 and 20 Litre.

PROPERTIES

Drying Time Surface dry in 2 hours, re-coateable after 4 - 6 hours under normal conditions.

Spread Rate 8 – 10 sq. metres per litre per coat dependent on surface porosity and texture.

Uses Suitable for the protection and decoration of exterior stucco, cement, stone, precast concrete, pebbledash, tryolean finish etc.

Biocide is incorporated in the paint formulation to protect against organic growths and the smooth nature of the film ensures minimal dirt pick-up and fast, easy application by brush, roller, or airless spray.

Preparation Repair all cracks and structural defects. Surface must be dry and free from loose and flaking material, dirt, grease and organic growth. If there is evidence of organic growth, vigorous cleaning, either manually or mechanically. Power washing is especially recommended if the substrate has rough contours.

Application Stir contents thoroughly, apply by brush or roller. Two coats are normally recommended for best results. Do not apply below 5° C or where the relative humidity may cause surface condensation, and where there is a threat of heavy rain.

Cleaning Clean all equipment with water immediately after use.

SPECIFICATIONS

Exterior Stucco Work, Cement, Concrete, Stone, Pebbledash, etc. Apply two coats as supplied. In enclosed areas the decoration of common brick should be avoided due to failure of adhesion caused by random element imposed by the variability of the bricks.

Previously-Painted Surfaces Thoroughly wash off dirt, grease etc. and remove all loose and flaking paint. Apply 2 to 3 coats of paint.

Distempered Surfaces

Remove all loose and flaking paint. Carry out necessary repairs. Apply a mist coat to consolidate the surface. Apply two to three coats of water paint. Thin as recommended.

Precautions

Store away from temperature extremes.

Use only in well ventilated areas during spraying. In case of insufficient ventilation during spraying wear suitable respiratory equipment.
Do not breath vapour / spray.
In case of contact with eyes, rinse immediately with plenty of water, seek medical advice.
Keep out of reach of children.

No Lead Added