

MAXACRYL

ACRYLIC MATT EMULSION

An interior, durable, water-borne matt emulsion based on a new-generation styrene acrylic resin. Maxacryl is a high-opacity, brilliant white, matt formulation. It has excellent scrub resistance properties.

AVAILABILITY

<i>Colour</i>	Brilliant White
<i>Packing</i>	5, 10 and 15 Litres.

PROPERTIES

<i>Uses</i>	Suitable for the decoration of interior walls & ceilings in stone, mortar, gypsum render and drywall boards.
<i>Spread Rate</i>	Up to 12 sq. metres per litre per coat depending on surface porosity and texture.
<i>Drying Time</i>	Touch dry in 2hrs and re-coatable after 4hrs under normal conditions.
<i>Application</i>	For brush or roller application where required by the type of surface, thin with up to 10% water. On very absorbent surfaces, Maxacryl used as mist coat may be thinned with up to 40% water. For airless spray application, thin with up to 20% water.
<i>Cleaning</i>	Clean all equipment with water immediately after use.

SPECIFICATIONS

<i>New Plaster, Plasterboard, Brickboard and Cement</i>	To the clean, dry, efflorescent-free surface, apply a mist coat (watered-down) coat of paint. Apply a further one to two coats of paint. Thin as recommended.
<i>Previously-painted Surfaces</i>	Thoroughly wash off dirt, grease etc. and remove all loose and flaking paint. Apply 2 to 3 coats of paint.
<i>Distempered Surfaces</i>	Remove all loose and flaking paint. Carry out necessary repairs. Apply a mist coat to consolidate the surface. Apply two to three coats of water paint. Thin as recommended.

Use only in well ventilated areas during spraying. In case of insufficient ventilation during spraying wear suitable respiratory equipment.
Do not breath vapour / spray.
In case of contact with eyes, rinse immediately with plenty of water, seek medical advice.
Keep out of reach of children.

No Lead Added