

MULTISEAL MASONRY PRIMER

An economical low opacity primer that seals surfaces such as new plaster, concrete, bricks, limestone and lime washed walls.

AVAILABILITY

| | |
|---------------------|-----------------------|
| <i>Colour Range</i> | Clear. |
| <i>Packing</i> | 5 Litre and 10 Litre. |

PROPERTIES

| | |
|--------------------|--|
| <i>Drying Time</i> | Touch dry in 2hrs and re-coatable after 6hrs under normal conditions. |
| <i>Spread Rate</i> | Up to 12 sq. metres per litre per coat depending on surface porosity and texture. |
| <i>Uses</i> | For application on exterior or interior surfaces to act as a sealing agent. Traditionally used as a diluent with exterior textured coatings. |
| <i>Preparation</i> | All surfaces must be free from mould growth, dirt and grease. Organic growth must be removed and the spores killed by the application of Macpherson's Anti Mould Solution at least 24hrs before and subsequently washed down with the active solution and allowed to dry before treatment. |
| <i>Application</i> | Supplied ready for use by brush or roller and should not be diluted. Apply sufficient Multiseal to satisfy the absorbency of the surface. When used as a diluent with textured exterior coatings, do not exceed more than 5 – 10% v/v. Mix well prior to use. |
| <i>Cleaning</i> | Clean all equipment with water immediately after use. |

Use only in well ventilated areas during spraying.
In case of insufficient ventilation during spraying wear suitable respiratory equipment.
Do not breath vapour / spray.
Wear suitable protective clothing, gloves and eye / face protection.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Keep out of reach of children.

No Lead Added