

Technical Data Sheet

PAINTS

PEARLTEX TEXTURED

A traditional, durable water borne matt exterior finish with a plastic vinyl resin base reinforced with mica and aggregates. The balance of the formulation provides a tough, weather- resistant face to combat the elements; flexibility to achieve maximum adhesion and protection against organic growth.

AVAILABLILITY

Colour Range White and Magnolia.

Packing 2.5Litre, 5 Litre, 10 Litre and 20 Litre.

PROPERTIES

Drying Time Surface dry in 2 hours, recoatable after 4 - 6 hours under normal conditions.

Spread Rate Up to 6 sq. metres per litre per coat depending on surface porosity and texture.

Uses Suitable for the protection and decoration of exterior stucco, cement, stone,

precast concrete, pebbledash, tryolean finish etc.

Preparation Repair all cracks and structural defects. Surface must be dry and free from loose

and flaking material, dirt, grease and organic growth. If there is evidence of organic growth, vigorous cleaning, either manually or mechanically. Power

washing is especially recommended if the substrate has rough contours.

Application Stir contents thoroughly, apply by brush or roller. Two coats are normally

recommended for best results. Do not apply below 5° C or where the relative humidity may cause surface condensation, and where there is a threat of heavy

rain.

Cleaning Clean all equipment with water immediately after use.

SPECIFICATIONS

Exterior Stucco Work, Cement, Concrete, Stone, Pebbledash, etc. Apply two coats as supplied. In enclosed areas the decoration of common brick should be avoided due to failure of adhesion caused by random element imposed by the variability of the bricks.

Previously-Painted Surfaces Thoroughly wash off dirt, grease etc. and remove all loose and flaking paint. Apply 2 to 3 coats of paint.

Distempered Surfaces Remove all loose and flaking paint. Carry out necessary repairs. Appy a mist

coat to consolidate the surface. Apply two to three coats of water paint. Thin as recommended.

Precautions

Store away from temperature extremes.

Use only in well ventilated areas during spraying. In case of insufficient ventilation during spraying wear suitable respiratory equipment.

Do not breath vapour / spray.

In case of contact with eyes, rinse immediately with plenty of water, seek medical advice. Keep out of reach of children.

No Lead Added

