

RAYLUX VINYL MATT EMULSION

An attractive matt finish with excellent opacity that provides good durability and produces a wipeable surface that is resistant to yellowing and fading.

AVAILABILITY

Colour Range Brilliant White and Magnolia

Packaging 2.5, 5, 10 and 15 Litres.

PROPERTIES

Drying Time Touch dry in 2hrs and re-coatable after 4hrs under normal conditions.

Spread Rate Up to 12 sq. metres per litre per coat depending on surface porosity and texture.

Uses Suitable for the decoration and preservation of interior walls & ceilings.

Application Supplied ready for use by brush, roller or conventional spray. For airless spray application, thin with up to 20% water. For brush or roller application where required by the type of surface, thin with up to 10% water. On very absorbent surfaces, the first coat may be thinned with up to 40% water.

Cleaning Clean all equipment with water immediately after use.

SPECIFICATIONS

New Plaster, Plasterboard, Brickboard and Cement To the clean, dry, efflorescent-free surface, apply a mist coat (watered-down) coat of paint. Apply a further one to two coats of paint. Thin as recommended.

Previously-Painted Surfaces Thoroughly wash off dirt, grease etc. and remove all loose and flaking paint. Apply 2 to 3 coats of paint.

Distempered Surfaces Remove all loose and flaking paint. Carry out necessary repairs. Apply a mist coat to consolidate the surface. Apply two to three coats of water paint. Thin as recommended.

Precautions Store away from temperature extremes.

Use only in well ventilated areas during spraying. In case of insufficient ventilation during spraying wear suitable respiratory equipment.
Do not breath vapour / spray.
In case of contact with eyes, rinse immediately with plenty of water, seek medical advice.
Keep out of reach of children.

No Lead Added