

TEXTURED FLOOR COATING – WATER-BASED

A water-based floor coating for interior and exterior use with fine dolomite particles. Ideal for protecting and decorating concrete, stone and tarmacked surfaces.

AVAILABILITY

<i>Colour Range</i>	Pastel Base and Base 950 to tint shades in the Paint Tinting System by Crown Paints.
<i>Packing</i>	10 litres.

PROPERTIES

<i>Composition:</i>	Styrene acrylic resin formulation with titanium dioxide and a blend of fillers.
<i>Drying Time</i>	Surface dry in 2-3 hours, re-coatable after 12 hours under normal conditions.
<i>Spread Rate</i>	5 - 8sq. metres per litre per coat dependent on surface porosity and texture when applied by roller or brush.
<i>Uses</i>	<p>A single-pack, water-based floor paint for the painting of a variety of natural surfaces. Its fine texture improves adhesion and imparts non-slip properties. Intended for foot traffic and light commercial use. The product is not intended to protect floors in industrial locations, warehouses with forklifting equipment, parking lots or where heavy machinery and heavy vehicular use is present. The product will NOT improve non-slip properties in steep ramps.</p>
<i>Preparation</i>	<p>Surface must be dry and free from loose and flaking material, dirt, grease and organic growth. If there is evidence of organic growth, vigorous cleaning, either manually or mechanically, (Power washing is especially recommended if the substrate has rough contours) is essential before sterilising the surface with Macpherson Anti Mould Solution.</p> <p>Applying one coat of Macpherson Adhesion Promoting Primer, diluted as per instructions, will improve adhesion.</p>
<i>Application</i>	Two coats are normally recommended for best results. The first coat may be diluted with 10-15% of clean water and the second coat with 5-10%. Do not apply below 10°C and where the relative humidity may cause surface condensation, or where there is a threat of heavy rain.

Cleaning

Clean all equipment with soap and water immediately after use.

Precautions

Store away from temperature extremes.

Use only in well ventilated areas during spraying. In case of insufficient ventilation during spraying wear suitable respiratory equipment.

Do not breath vapour / spray.

In case of contact with eyes, rinse immediately with plenty of water, seek medical advice.

Keep out of reach of children.

No Lead Added